

SECTION 1 : Identification of the substance/preparation and of the company / undertaking**(a) GHS product identifier**

Garreco Print Model 3D Pro Resin (Beige and Grey)

(e) Emergency phone number

CHEMTRAC 1-800-424-9300

CCN9105**(b) Other means of identification**

N/A

(c) Recommended use of the chemical and restrictions on use

For professional 3D printing for dental applications.

(d) Supplier's details

Garreco, LLC.

PO Box 1258

Heber Springs, AR 72543

Phone: 1-800-334-1443

SECTION 2: Hazards identification**(a) GHS classification of the substance/mixture**

Aquatic Chronic 4: Hazardous to the aquatic environment, long-term hazard, Category 4, H413

Skin Sens. 1B: Sensitisation, skin, Category 1B, H317

(b) Label Elements**Hazard statements**

Aquatic Chronic 4: H413 - May cause long lasting harmful effects to aquatic life.

Skin Sens. 1B: H317 - May cause an allergic skin reaction.

Precautionary statements

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

P272: Contaminated work dothing should not be allowed out of the workplace.

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352: IF ON SKIN: Wash with plenty of water.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively.

Hazard Symbol(s)

Exclamation Mark

Signal Word(s)

Warning

(c) Other hazards which do not result in classificationContains diisodecyl phenyl phosphite, Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide, pentaerythritol tetraacrylate.
Product fails to meet PBT/vPvB criteria

SECTION 3: Composition/information on ingredients

(a) Chemical(s) Identity: (b) Common Name:	(c) CAS No.	Mixture: Concentration (Percentage)
Esterification products of 4,4'-isopropylidenediphenol, ethoxylated and 2-methylprop-2-enoic acid	41637-38-1	85 - <100 %
Pentaerythritol tetraacrylate	4986-89-4	3 - 9%
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	75980-60-8	0.5 - <2 %
Cyclohexane	110-82-7	0.01 - <0.1%
Toluene	108-88-3	0.01 - <0.1%
N-butyl acetate	123-86-4	0.01 - <0.1%

SECTION 4: First-aid measures

(a) Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation: This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

By skin contact: Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact: Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after deaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration: Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

(b) Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

(c) Indication of any immediate medical attention and special treatment needed:

ND

SECTION 5: Fire-fighting measures**(a) Suitable extinguishing media:**

Product is non-flammable under normal conditions of storage, manipulation and use, but the product contains flammable substances. In the case of inflammation as a result of improper manipulation, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems. IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

(b) Special hazards arising from the chemical or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

(c) Special protective equipment and precautions for fire-fighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit, ...) in accordance with Directive 89/654/EC.

SECTION 6: Accidental release measures**(a) Personal precautions, protective equipment and emergency procedures:**

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

(b) Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

(c) Methods and material for containment and cleaning up:

It is recommended: Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

SECTION 7: Handling and storage

(a) Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B. - Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks, ...) and transfer at slow speeds to avoid the creation of electrostatic charges. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

(b) Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5° C

Maximum Temp.: 30° C

B. - General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food.

SECTION 8: Exposure controls/Personal protection

(a) Control parameters:

Chemical	ACGIH	OSHA
	TLV-TWA	PEL TWA
Cyclohexane	100 ppm	300 ppm (1050 mg/m ³)
Toluene	20 ppm	200 ppm
N-butyl acetate	50 ppm (238 mg/m ³)	150 ppm (710 mg/m ³)

(b) Appropriate Engineering Controls:

Provide emergency shower and eyewash stations in case of exposure.

(c) Individual protection measures:

MANDATORY RESPIRATORY: Wear, at minimum, a NIOSH/OSHA approved half-face respirator with a vapor filter that conforms to EN 405:2002+A1:2010. Replace filter when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

MANDATORY HAND PROTECTION: Use protective gloves against minor risks. Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN 420:2004+ A1:2010 and EN ISO 374-1:2016+A1:2018

MANDATORY FACE PROTECTION: Use panoramic glasses against splash/projections. Clean daily and disinfect periodically according to the manufacturer 's instructions. use if there is a risk of splashing. Recommend using protection conforming to EN 166:2022 EN ISO 4007:2018.

SECTION 9: Physical and chemical properties

(a) Appearance:	Viscous Liquid
(b) Odor:	Resin
(c) Odor threshold:	ND
(d) pH:	~ 6 - 8 (at 100%)
(e) Melting point / freezing point:	ND
(f) Initial boiling point and boiling range:	ND
(g) Flash point	Non Flammable (>60° C)
(h) Evaporation rate (BuAc=1):	ND
(i) Flammability:	ND
(j) Upper/lower flammability or explosive limits:	ND
(k) Vapor Pressure:	ND
(l) Density at 20° C:	1127.3 kg/m ³
(m) Relative density:	1.13
(n) Solubility:	ND
(o) Partition coefficient: n-octanol/water:	ND
(p) Auto-ignition temperature:	260° C
(q) Decomposition temperature:	ND
(r) Viscosity:	ND

SECTION 10: Stability and reactivity

(a) Reactivity:	No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.
(b) Chemical stability:	Stable
(c) Possibility of hazardous reactions:	Low
(d) Conditions to avoid:	Avoid strong acids, alkalis, or strong bases. Avoid Impact to Oxidizing materials.
(f) Hazardous decomposition products:	Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO ₂), carbon monoxide and other organic compounds.

SECTION 11: Toxicological information

Acute toxicity	Based on available data, classification is not met, however, does contain substances to this effect
Skin corrosion/irritation	Based on available data, classification is not met, however, does contain substances to this effect
Serious Eye Damage / Irritation	Based on available data, classification is not met, however, does contain substances to this effect
Respiratory or skin sensitization	Based on available data, classification is not met, however, does contain substances to this effect
Germ cell mutagenicity	Based on available data, classification is not met, however, does contain substances to this effect
Carcinogenicity	Based on available data, classification is not met, however, does contain substances to this effect
Reproductive toxicity	Based on available data, classification is not met, however, does contain substances to this effect
STOT-single exposure	Based on available data, classification is not met, however, does contain substances to this effect
STOT-repeated exposure	Based on available data, classification is not met, however, does contain substances to this effect
Aspiration Hazard	Based on available data, classification is not met, however, does contain substances to this effect

(a) Exposure route:	inhalation, skin and/or eye contact
(b) Symptoms related to the physical, chemical and toxicological characteristics:	difficulty breathing, rashes or irritations
(c) Delayed and immediate effects and also chronic effects from short and long tem exposure:	difficulty breathing, rashes or irritations

SECTION 11: Toxicological information (Continued)

(d) Numerical measures of toxicity:

CHEMICAL	CAS NO.	LD50 ORAL	LD50 DERMAL	LC50 INHALATION
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	75980-60-8	5500 mg/kg (rat)	N/A	N/A
Cyclohexane	110-82-7	5100 mg/kg (rat)	N/A	N/A
Toluene	108-88-3	5580 mg/kg (rat)	12124 mg/kg (rat)	28.1 mg/L (4h rat)
N-butyl acetate	123-86-4	12789 mg/kg (rat)	14112 mg/kg (rabbit)	23.4 mg/L (4h rat)

SECTION 12: Ecological information

(a) Ecotoxicity:

CHEMICAL	ACUTE TOXICITY		TIME (HOURS)	GENUS
	LC50	>1 - 10 mg/L		
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	LC50	>1 - 10 mg/L	96	FISH
	EC50	>1 - 10 mg/L	48	CRUSTACEAN
	EC50	>1 - 10 mg/L	72	ALGAE
Cyclohexane	LC50	>0.1 - 1 mg/L	96	FISH
	EC50	>0.1 - 1 mg/L	48	CRUSTACEAN
	EC50	>0.1 - 1 mg/L	72	ALGAE
Toluene	LC50	5.5 mg/L	96	FISH
	EC50	3.78 mg/L	48	CRUSTACEAN
	EC50	125 mg/L	48	ALGAE
N-butyl acetate	LC50	Non-applicable	96	FISH
	EC50	Non-applicable	24	CRUSTACEAN
	EC50	675 mg/L	72	ALGAE

(b) Persistence and degradability:

CHEMICAL	DEGRADABILITY		BIODEGRADABILITY	
	BOD5	Non-applicable	CONCENTRATION	100 mg/L
Cyclohexane	COD	Non-applicable	PERIOD	28 days
	BOD5/COD	Non-applicable	% BIODEGRADABLE	0%
	BOD5	2.5 g O2/g	CONCENTRATION	100 mg/L
Toluene	COD	Non-applicable	PERIOD	14 days
	BOD5/COD	Non-applicable	% BIODEGRADABLE	100%
	BOD5	Non-applicable	CONCENTRATION	Non-applicable
N-butyl acetate	COD	Non-applicable	PERIOD	5 days
	BOD5/COD	Non-applicable	% BIODEGRADABLE	84%

SECTION 12: Ecological information (CONTINUED)

(c) Bioaccumulative potential

CHEMICAL	BIOACCUMULATION POTENTIAL	
Cyclohexane	BCF	66
	POW LOG	3.44
	POTENTIAL	MODERATE
Toluene	BCF	13
	POW LOG	2.73
	POTENTIAL	LOW
N-butyl acetate	BCF	4
	POW LOG	1.78
	POTENTIAL	LOW

(d) Mobility in soil:

CHEMICAL	ABSORPTION/DESORPTION		VOLATILITY	
Cyclohexane	KOC	Non-applicable	HENRY	Non-applicable
	CONCLUSION	Non-applicable	DRY SOIL	Non-applicable
	SURFACE TENSION	2.465E-2 N/m (25° C)	MOIST SOIL	Non-applicable
Toluene	KOC	178	HENRY	672.8 Pa m ³ /mol
	CONCLUSION	Moderate	DRY SOIL	Yes
	SURFACE TENSION	2.793E-2 N/m (25° C)	MOIST SOIL	Yes
N-butyl acetate	KOC	Non-applicable	HENRY	Non-applicable
	CONCLUSION	Non-applicable	DRY SOIL	Non-applicable
	SURFACE TENSION	2.478E-2 N/m (25° C)	MOIST SOIL	Non-applicable

Product fails to meet PBT /vPvB criteria

(e) Other adverse effects:

Not described

SECTION 13: Disposal considerations

CODE	DESCRIPTION	WASTE CLASS (Regulation (EU) No. 1357 / 2014)
20 01 27	paint, inks, adhesives and resins containing hazardous substances	Dangerous

TYPE OF WASTE (Regulation (EU) No 1357 / 2014)

HP14 Ecotoxic

Consult with local waste authorities, regulations, and/or a authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. otherwise, it will be processed as non-dangerous residue.

We do not recommended disposal down the drain. In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: Transport information

(a) UN Number

This product is not regulated as a hazardous material by neither the United States (DOT) Transportation regulations nor Canadian Transportation of Dangerous Goods.

(b) UN Proper shipping name

NA

(c) Transport hazard class(es)

NA

(d) Packing Group

NA

(e) Environmental hazards

NA

(f) Transport in bulk

NA

(g) Other Information

SECTION 15: Regulatory information

SARA Reporting Requirements:

NA

SARA Threshold Planning Quantity:

NA

TSCA Inventory Status:

ND

Other Federal Requirements:

NA

Other Canadian Regulations:

NA

State Regulatory Information:

NA

SECTION 16: Other information

PREPARED BY: Kristofer Mainar
GAR QMS SDS REFERENCE: A853

REVISION NUMBER: 220309

CHANGES FROM PREVIOUS VERSION: INITIAL VERSION

ABBREVIATIONS

NA Not Applicable	LD Lethal Dose
ND Not Determined	TC Toxic Concentration
NE Not Established	TD Toxic Dose
ppm parts per million	BOD Biological Oxygen Demand
G Gallon	COD Chemical Oxygen Demand
mg Milligram	Lo Lowest
L Liter	ThOD Theoretical Oxygen Demand
gm Gram	TLm Threshold Limit
mol Mole	IC Inhibitory Concentration
kg Kilogram	DOC Dissolved Organic Carbon
μ Micro	H Hours
mm Millimeter	M Months
p Pico	D Days
Pa Pascals	Y Years
c cento	W Weeks
LC Lethal Concentration	

ACGIH American Conference of Governmental Industrial Hygienist
 CPR Controlled Product's Regulation
 DSL Canadian Domestic Substances List
 NDSL Canadian Non-domestic Substance List
 IARC International Agency for Research for Cancer
 NOEL No Observed Effect Level
 NOAEL No Observed Adverse Effect Level
 OSHA Occupational Safety and Health Administration
 PEL Permissible Exposure Limit
 TLV Threshold Limit Value

THIS MATERIAL SAFETY DATA SHEET IS PREPARED IN COMPLIANCE WITH FEDERAL REGULATIONS (29 CFR 1910.1200) OF CHEMICALS AND THE GLOBALLY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELLING REVISION 5. ANY APPLICABLE STATE AND LOCAL REGULATIONS SHOULD BE CONSULTED.

THE ABOVE INFORMATION MAY BE BASED IN PART ON INFORMATION PROVIDED BY COMPONENT SUPPLIERS AND IS BELIEVED TO BE CORRECT AS OF THE DATE HEREOF. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY USE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OF THESE DATA, THE RESULTS TO BE OBTAINED FROM THE USE OF THE MATERIAL, OR THE HAZARDS CONNECTED WITH SUCH USE. SINCE THE INFORMATION CONTAINED HEREIN MAY BE APPLIED UNDER CONDITIONS BEYOND OUR CONTROL AND WITH WHICH WE MAY BE UNFAMILIAR, AND SINCE DATA MADE AVAILABLE SUBSEQUENT TO THE DATE HEREOF MAY SUGGEST MODIFICATION OF THE INFORMATION, WE ASSUME NO RESPONSIBILITY FOR THE RESULT OF ITS USE. THIS INFORMATION AND MATERIAL IS FURNISHED ON THE CONDITION THAT THE PERSON RECEIVING IT SHALL MAKE HIS/HER OWN DETERMINATION AS TO THE SUITABILITY OF THE MATERIAL FOR HIS/HER PARTICULAR PURPOSE AND ON THE CONDITION THAT HE/SHE ASSUME THE RISK OF HIS/HER USE THEREOF.