Safety Data Sheet

Form No. A412 **Date Prepared:** 2/15/2016

SECTION 1: Identification of the substance/preparation and of the company / undertaking

(a) GHS product identifier

Garreco Axcent Auto Cure Repair Liquid

(e) Emergency phone number

CHEMTREC 1-800-424-9300

(b) Other means of identification

NA

(c) Recommended use of the chemical and restrictions on use

For professional dental applications.

(d) Supplier's details

Garreco. LLC. 430 Hiram Road Heber Springs, AR 72543

Phone: 1-800-334-1443

SECTION 2: Hazards identification

(a) GHS classification of the substance/mixture

Substance Name

- Methyl Methacrylate Monomer
- 2. Ethylene Glycol Dimethacrylate

(b) Label Elements

Hazard statements

Causes skin irritation

Causes severe eve irritations

May cause an allergic skin reaction

May cause respiratory irritation. May cause drowsiness or dizziness.

Highly flammable liquid and vapor.

Precautionary statements

Wash face, hands and any exposed skin thoroughly after handling Wear protective gloves/protective clothing/eye protection/face protection

Avoid breathing dust/fume/gas/mist/vapors/spray

Contaminated work clothing should not be allowed out of the workplace

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces.--No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof equipment

Use only non-sparking tools

Take precautionary measures against static discharge Keep cool

Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. Get medical attention if irritation occurs.

If skin irritation or rash occurs: Get medical advice/attention

IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

In case of fire: Use CO2, dry chemical, or foam for extinction.

Storage

Store in a well-ventilated place. Keep container tightly closed.

Store locked up

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazard Symbol(s) Signal Word(s)

Flame Danger

Exclamation mark

(c) Other hazards which do not result in classification

Harmful to aquatic life with long lasting effects

Harmful to aquatic life

Mixture:

Page 1 of 6

SECTION 3: Composition/information on ingredients

(a) Chemical(s) Identity:

Safety Data Sheet

Form No. A412 **Date Prepared:** 2/15/2016 **Concentration (Percentage)** (b) Common Name: (c) CAS No.

1. Methyl Methacrylate monomer 80-62-6 >90% 2. Ethylene Glycol Dimethacrylate 97-90-5 2.5 - 10%

SECTION 4: First-aid measures

(a) Description of first aid measures:

IF IN EYES: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

IF ON SKIN (OR HAIR): Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Seek medical attention if irritation develops.

IF INHALED: Remove to fresh air. If rapid recovery does not occur, transport to nearest medical facility for additional treatment.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Seek medical advice.

(b) Most important symptoms and effects, both acute and delayed:

Overexposure by inhalation may cause CNS depression-drowsiness, dizziness, confusion or loss of coordination. May cause skin and eye irritation. May cause allergic skin reaction. Will cause gastrointestinal tract irritation.

(c) Indication of any immediate medical attention and special treatment needed:

Note to Physicians: Treat symptomatically. Can cause allergic response in susceptible or hypersensitive individuals upon repeated or prolonged exposure.

SECTION 5: Fire-fighting measures

(a) Suitable extinguishing media:

Foam, Dry Chemical, Carbon Dioxide.

Unsuitable Extinguishing Media: Water jet.

(b) Special hazards arising from the chemical or mixture:

Vapors may travel to source of ignition and flash back.

Sensitivity to Static Discharge: Take precautionary measures against static discharge. Flammable mixtures of this product are readily ignited even by static discharge.

(c) Special protective equipment and precautions for fire-fighters:

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. In the event of fire, cool the endangered containers with water.

SECTION 6: Accidental release measures

(a) Personal precautions, protective equipment and emergency procedures:

Personal Precautions: Wear protective clothing as described in Section 8 of this safety data sheet. Remove all sources of ignition. The wet contaminated surface may be slippery.

Environmental Precautions: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). See section 12 for additional ecological information.

(b) Methods and material for containment and cleaning up:

Methods for Containment: Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite).

Methods for Cleaning Up: Use clean non-sparking tools to collect absorbed material. Sweep up absorbed material and shovel into suitable containers for disposal. Discard any product, residue, disposable container or liner in full compliance with federal, state, and local regulations. For waste disposal, see section 13 of the SDS. Wash spill area with a mild detergent.

Safety Data Sheet

2/15/2016 Form No. A412 **Date Prepared:**

SECTION 7: Handling and storage

(a) Precautions for safe handling:

Advice on Safe Handling: Handle in accordance with good industrial hygiene and safety practice. Wear appropriate personal protective equipment. Wash face, hands, and any exposed skin thoroughly after handling. Keep away from heat/sparks/open flames/hot surfaces. --No smoking. Take precautionary measures against static discharges. Ground container and transfer equipment to eliminate static electric sparks. Use spark-proof tools and explosion-proof equipment. Avoid breathing vapors or mists. Contaminated work clothing should not be allowed out of the workplace. Use only in well-ventilated areas. Keep containers closed when not in use. Keep cool.

(b) Conditions for safe storage, including any incompatibilities:

Storage Conditions: Keep container tightly closed and store in a cool, dry and well-ventilated place. Store between 16°-26°C (69°-79°F). Store locked up. Protect from sunlight. Protect from damp. Store away from heat and incompatible materials.

Incompatible Materials: Organic peroxides, Reducing agent, Strong oxidizing agents.

SECTION 8: Exposure controls/Personal protection

(a) Control parameters:

ACGIH TLV OSHA PEL NIOSH IDLH 1. Methyl Methacrylate STEL: 100 ppm TWA: 100 ppm IDLH: 1000 ppm TWA: 50 ppm TWA: 410 mg/m³ TWA: 100 ppm (vacated) TWA: 410 mg/m³

(b) Appropriate Engineering Controls:

Good ventilation is required.

(c) Individual protection measures:

EYE PROTECTION: Splash googles or safety glasses.

SKIN AND BOODY PROTECTIONS: Polyethylene / Nitrile gloves. Do not use cotton gloves. Rubber boots. Polyethylene apron is recommended.

RESPIRATORY: Ensure adequate ventilation, especially in confined areas. Use NIOSH approved air-purifying respirator if the potential to exceed established exposure limits exists.

GENERAL HYGIENE CONSIDERATIONS: Handle in accordance with good industrial hygiene and safety practice.

SECTION 9: Physical and chemical properties

Colorless liquid (a) Appearance: Characteristic (b) Odor: Not determined (c) Odor threshold: Not determined (d) pH: (e) Melting point / freezing point: Not determined

(f) Initial boiling point and boiling range: 100 °C / 212 °F @ 760 mm HG 8 °C / 46.4 °F Tag Closed Cup (g) Flash point (butyl acetate=1)

(h) Evaporation rate (BuAc=1):

(i) Flammability:

(j) Upper/lower flammability or explosive limits:

(k) Vapor Pressure: (I) Vapor density: (m) Relative density: (n) Solubility:

(o) Partition coefficient: n-octanol/water:

(p) Auto-ignition temperature: (q) Decomposition temperature: (r) Viscosity:

(Air=1)-1 (1=Water) Slightly soluble, Not determined in other solvents

> Not determined 430°C / 806°F Not determined Not determined

Not determined 12 / 1.5%

Not determined

Safety Data Sheet

Form No. A412 Date Prepared: 2/15/2016

SECTION 10: Stability and reactivity

(a) Reactivity: Not reactive under normal conditions.

(b) Chemical stability: Stable under recommended storage conditions.

(c) Possibility of hazardous reactions:

Prolonged exposure to elevated temperatures which can cause premature

polymerization and release methyl methacrylate vapors.

(d) Conditions to avoid: Temperatures >35 °C (95 °F).

(e) Incompatible Materials:

Organic peroxides, Reducing agent, Metallic Redox systems, Strong

oxidizing agents.

(f) Hazardous decomposition products:

None known based on information supplied

SECTION 11: Toxicological information

Acute toxicity Yes

Skin corrosion/irritationCauses skin irritation. May cause allergic skin reaction.

Serious Eye Damage / Irritation Causes serious eye irritation.

Respiratory or skin sensitizationMay cause irritation to the mucous membranes and upper respiratory tract.

Germ cell mutagenicity Not determined

Carcinogenicity Methyl Methacrylate Monomer - IARC - Group 3

Reproductive toxicity

Not determined

STOT-single exposure May cause respiratory irritation. May cause drowsiness or dizziness.

STOT-repeated exposure Not determined
Aspiration Hazard Not determined

(a) Exposure route: Please see above for normal exposure routes.

(b) Symptoms related to the physical, chemical and toxicological characteristics:

Please see section 4 of this SDS for symptoms.

(c) Delayed and immediate effects and also chronic effects from short and long tem exposure:

Please see above for effects.

(d) Numerical measures of toxicity: Oral LD50 >7872 mg/kg (rat)

Dermal LD50 >5 g/kg (rabbit)

Inhalation LC50 4632 ppm (rat) 4 h, 400 ppm (rat) 1 hr

SECTION 12: Ecological information

(a) Ecotoxicity:

1.Methyl Methacrylate Aquatic Plants Fish Crustacea

170: 96h Pseudokirchneriella subcapitata mg/L EC50 243-275: 96 h Pimephales promelas mg/L LC50 flow-through 125.5-190.7: 96 h Pimephales promelas mg/L LC50 static 170-206: 96 h Lepomis macrochirus mg/L LC50 flow-through 153.9-341.8: 96 h Lepomis macrochirus mg/L LC50 static 79: 96 h Oncorhynchus mykiss mg/L LC50 static 326.4-426-9: 96 h Poecilia

reticulata mg/L LC 50 static

69: 48 h Daphnia magna mg/L EC50

(b) Persistence and degradability:

Not readily biodegradable

(c) Bioaccumulative potential

Not determined

(d) Mobility in soil:

Methyl Methacrylate Monomer - Partition Coefficient: 0.7

(e) Other adverse effects:

Not determined

Safety Data Sheet

Form No. A412 **Date Prepared: 2/15/2016**

SECTION 13: Disposal considerations

Product:

Recommendation

Disposal of Wastes: Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging: Disposal should be in accordance with applicable regional, national and local laws and regulations.

Methyl Methacrylate - RCRA: U162 - RCRA - Basis for Listing: Included in waste stream: F039 - RCRA - U Series

Wastes: U162

California Hazardous Waste Status: Toxic, ignitable

SECTION 14: Transport information

(a) UN Number

UN1247

(b) UN Proper shipping name

Methyl methacrylate monomer, stabilized

(c) Transport hazard class(es)

3

(d) Packing Group

Ш

(e) Environmental hazards

Not determined

(f) Transport in bulk

Not determined

(g) Other Information

Not determined

SECTION 15: Regulatory information

SARA Reporting Requirements:

Yes

SARA Threshold Planning Quantity:

1.00%

TSCA Inventory Status:

Not determined

Other Federal Requirements:

CERCLA - Hazardous Substances RQs: 1000 lb - Reportable Quantity: RQ

1000 lb final RQ, RQ 454 kg final RQ

CWA - CWA - Reportable Quantities: 1000 lb

Other Canadian Regulations:

Not determined

State Regulatory Information:

U.S. State Right-to-Know Regulations: New Jersey, Massachusetts,

Pennsylvania

Safety Data Sheet

Form No. A412 **Date Prepared: 2/15/2016**

SECTION 16: Other information

PREPARED BY: Kathryn Harris

GAR QMS SDS REFERENCE: A397

HAZARDOUS MATERIAL IDENTIFICATION (HMIS) RATING:

Health Not determined Flammability Not determined Reactivity Not determined Other Not determined

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) HAZARD IDENTIFICATIN RATING:

Health Not determined
Flammability Not determined
Reactivity Not determined
Special Information Not determined

REVISION NUMBER: 160215

CHANGES FROM PREVIOUS VERSION: INITIAL VERSION

ABBREVIATIONS

NA Not Applicable LD Lethal Dose

ND Not Determined TC Toxic Concentration

NE Not Established TD Toxic Dose

ppm parts per million BOD Biological Oxygen Demand G Gallon COD Chemical Oxygen Demand

mg Milligram Lo Lowest

L Liter ThOD Theoretical Oxygen Demand

gm Gram TLm Threshold Limit
mol Mole IC Inhibitory Concentration
kg Kilogram DOC Dissolved Organic Carbon

μ Micro
 mm Millimeter
 p Pico
 Pa Pascals
 c cento
 H Hours
 M Months
 D Days
 Y Years
 W Weeks

LC Lethal Concentration NOEL No Observed Effect Level

ACGIH American Conference of Governmental Industrial Hygienist

NOAEL No Observed Adverse Effect Level

CPR Controlled Product's Regulation

NDSL Canadian Non-domestic Substance List
IARC International Agency for Research for Cancer
OSHA Occupational Safety and Health Administration

DSL Canadian Domestic Substances List PEL Permissible Exposure Limit

TLV Threshold Limit Value

THIS MATERIAL SAFETY DATA SHEET IS PREPARED IN COMPLIANCE WITH FEDERAL REGULATIONS (29 CFR 1910.1200)
OFCHEMICALS AND THE GLOBALLY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELLING REVISION 5. ANY APPLICABLE
STATE AND LOCAL REGULATIONS SHOULD BE CONSULTED. THE ABOVE INFORMATION MAY BE BASED IN PART ON
INFORMATION PROVIDED BY COMPONENT SUPPLIERS AND IS BELIEVED TO BE CORRECT AS OF THE DATE HEREOF.
HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY USE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS
TO BE IMPLIED REGARDING THE ACCURACY OF THESE DATA, THE RESULTS TO BE OBTAINED FROM THE USE OF THE
MATERIAL, OR THE HAZARDS CONNECTED WITH SUCH USE. SINCE THE INFORMATION CONTAINED HEREIN MAY BE APPLIED
UNDER CONDITIONS BEYOND OUR CONTROL AND WITH WHICH WE MAY BE UNFAMILIAR, AND SINCE DATA MADE AVAILABLE
SUBSEQUENT TO THE DATE HEREOF MAY SUGGEST MODIFICATION OF THE INFORMATION, WE ASSUME NO RESPONSIBILITY
FOR THE RESULT OF ITS USE. THIS INFORMATION AND MATERIAL IS FURNISHED ON THE CONDITION THAT THE PERSON
RECEIVING IT SHALL MAKE HIS/HER OWN DETERMINATION AS TO THE SUITABILITY OF THE MATERIAL FOR HIS/HER
PARTICULAR PURPOSE AND ON THE CONDITION THAT HE/SHE ASSUME THE RISK OF HIS/HER USE THEREOF.